



The project: Painting mineral surfaces

Mineral façade surfaces should be ideally coated with silicate paints. Silification with the surface produces an extremely resistant bond. The silicate paint penetrates the pores in the surface thanks to its fine chemical structure. Silicate paints thus not only provide a coating, but also a lasting bond with the façade surface.

The optimum KRAUTOL system solution:



Silikat Fixativ
Priming and thinner
concentrate for silicate
paints



Silikat Fassade
Weather-resistant silicate
façade paint



KRAUTOL®

PROFESSIONAL

This is how it works: an optimum result in a few steps



Preparation and cleaning

Clean the façade with a pressure washer and completely remove any dirt or stains.

Leave façade to dry out completely after cleaning, so the subsequent primer can penetrate the façade more effectively.



Primer

Prime the façade with **Silikat Fixativ**. This high-quality primer strengthens the surface, ensuring uniform absorption. This brings the advantage that the façade paint dries evenly and adheres securely while less paint is consumed.

Allow façade to dry thoroughly again after priming.



Prime and finish coat

Pre-treat the façade with Silikat Fassade (diluted with a maximum of 5% water and Silikat Fixativ). The low viscosity of the paint ensures good penetration behaviour, thus achieving effective adhesion in the final coat.

Leave primer coat to dry out thoroughly. Then apply undiluted **Silikat Fassade**.



Other façade projects

Simply scan the QR code with your smartphone or tablet and access additional information.

12/2017

Systematic façade protection